## Jakeuchi

TW40
Wheel Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567 Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

Operating Weight: 7,275 lbs
Tip Load, Straight: 5,842 lbs
Bucket breakout force: 7,126 lbs
HP / RPM: 39.4 hp / 2,800 rpm
Travel Speed (Max): 12.4 gpm
Auxiliary Flow: 10.3 gpm

Maximum Height to Bucket pin: 9' 7.7" Height: (Canopy) 8' / (Cab) 8' 2"

Articulation: 40 /40

Lift Capacity @ G. L.: 5,260 lb Reach fully raised: 2' 8.5"

STANDARD EQUIPMENT

Back-Up Alarm

Front Working Lights

Rear Working Lights

Inching Pedal

Front Limited Slip Axle 45%

Auxiliary Hydraulic Lines
Replaceable Bushings
Bucket Float

Automatic Bucket Positioning

Heavy Duty Hydraulic SSL Style Quick Attach Coupler

Center Pivot Steering

Heavy Duty 31x15.5-15 Contruction Tire Assembly

	Optional heated Cab features front/rear wiper and rear defrost	
	BASE MACHINE WITH STANDARD EQUIPMENT	
Factory Code	Description	Suggested List Price
TW40	TW40 with Foldable ROPS Canopy and Tires	\$53,500
TW40C	TW40 with Cab with Heat and Tires	\$58,000

### BASE MACHINE PRICE DOES NOT INCLUDE ATTACHMENTS

	ATTACHMENTS	
BTW4060 BTW4060A BTW4060B	60" General Purpose Bucket (0.66 cu. Yd) for TW40 with SSL Mount 60" Bolt on Blade for BTW4060 (note: not compatible with bolt on blade)	\$2,300 \$282 \$643
	FIELD INSTALLED OPTIONS	

## Jakeuchii

TW65
Wheel Loader

**SERIES 2** 

519 Bonnie Valentine Way, Pendergrass, GA 30567 Tel:706-693-3600 Fax:706-693-3725

Maximum Height to Bucket Pin: 10 ft 4.6 in

www.takeuchi-us.com

HP / RPM: 73 / 2200

Height: 8 ft 9.8 in

Articulation: 40 /40

Auxiliary Flow: 16.4 gpm

Reach Fully Raised: 24"

Operating Weight: 11,354 lbs

Tip Load, Straight: 9,171 lbs

Travel Speed (Max): 12.4 mph

Lift Capacity @ G. L.: 10,319 lbs

Bucket Breakout Force: 11,600 lbs

### STANDARD EQUIPMENT

Enclosed cab w/ air conditioner, heat, front and rear widshield wiper,

front and rear washer, rear window defrost

LCD Gauge panel with muilti-function operator information center

with diagnostics and anti-theft capabilities

Deluxe susepsnion seat

Pilot operator loader joystick control

EPA Final Tier 4 turbocharged engine with DOC and engnie monitoring system

Side by side radiator and hydraulic oil cooler

Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick

100% Front and rear differentioal lock

Euro style attachment mount with hydraulic coupler

Bucket float

Mechanical bucketpositioning

Safety features include: ROPS/FOPS enclosed cab, back up alarm, lights retractabel seatbelt, control lockout, and deluxe lighting packae (front and rear working lights, front driving lights, front and rear hazard and directional indicators)

#### ORDER PROCEDURE

### ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

	BASE MACHINE WITH STANDARD EQUIPMENT			
Factory Code	Description	Suggested List Price		
TW65C2	TW65 Cab	\$80,500		
TW65C2HS	TW65 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control	\$84,700		
TW65C2HF	TW65 Cab, High Flow Auxiliary Hydraulics (26 gpm)	\$85,700		
TW65C2HH	TW65 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control	\$89,900		
	BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES			
	TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)			
BTW65TIREHD BTW65TIREF	Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy) Floatation Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$3,395 \$3,950		
ATTACHMENTS				
BTW5077 BTW5077A BTW8082 BTW8082A BTWPF48 BTWUNIADP	77" Construcion Combo Bucket (1.05 cu. Yd) for TW65/TW80 82" Bolt on Blade for BTW5077 81.5" General Purpose Bucket (1.3 cu. Yd) for TW80 82" Bolt-on Blade for BTW8082 48" Combo Fork Assy for all TW's Combo Hitch to Universal SSL Adapter TW50/60/65/80 FIELD INSTALLED OPTIONS	\$2,520 \$370 \$2,520 \$370 \$2,300 \$2,200		
1914199948	3" Retractable seat belt in lieu of standard 2"	\$91		

# Jakeuchi

TW80
Wheel Loader
SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567 Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

Operating Weight: 12,700 lbs Tip Load, Straight: 10,065 lbs Bucket Breakout Force: 12,287 lbs HP / RPM: 73 / 2200 Travel Speed (Max): 12.4 mph

Auxiliary Flow: 16.4 gpm

Maximum Height to Bucket Pin: 11 ft 1 in

Height: 8 ft 11.5 in Articulation: 40 /40

Lift Capacity @ G. L.: 12,287 lbs Reach Fully Raised: 29"

#### STANDARD EQUIPMENT

Enclosed cab w/ air conditioner, heat, front and rear widshield wiper,

front and rear washer, rear window defrost

LCD Gauge panel with muilti-function operator information center

with diagnostics and anti-theft capabilities

Deluxe susepsnion seat

Pilot operator loader joystick control

EPA Final Tier 4 turbocharged engine with DOC and engnie monitoring system

Side by side radiator and hydaulic oil cooler

Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick

100% Front and rear differentioal lock

Euro style attachment mount with hydralulic coupler

Bucket float

Mechanical bucket positioning

Safety features include: ROPS/FOPS enclosed cab, back up alarm, lights retractabel seatbelt, control lockout, and deluxe lighting packae (front and rear working lights, front driving lights, front and rear hazard and directional indicators)

#### ORDER PROCEDURE

### ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

Factory Code	BASE MACHINE WITH STANDARD EQUIPMENT	Currented List Drice		
Factory Code	Description	Suggested List Price		
TW80C2	TW80 Cab	\$89,500		
TW80C2HS	TW80 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control	\$93,700		
TW80C2HF	TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm)	\$94,700		
TW80C2HH	TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control	\$98,900		
	BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES			
	TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)			
BTW65TIREHD BTW65TIREF	Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy) Floatation Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$3,395 \$3,950		
ATTACHMENTS				
BTW8082 BTW8082A BTWPF48 BTWUNIADP	81.5" General Purpose Bucket (1.3 cu. Yd) for TW80 82" Bolt-on Blade for BTW8082 48" Combo Fork Assy for all TW's Combo Hitch to Universal SSL Adapter TW50/60/65/80 FIELD INSTALLED OPTIONS	\$2,520 \$370 \$2,300 \$2,200		
1914199948	3" Retractable seat belt in lieu of standard 2"	\$91		